















Easy to use, portable and powerful!

The VP series transfer pumps from TRIS are the original transferpumps useable for many fluids from (hydraulic) oil(s) to ammonia. The VP-06 and VP-20 can operate up to 20 Bar making it the ideal partner in transferring fluids into cooling systems. The VP-05, our smalles transfer pump, and can operate up to 8 Bar working pressure.

How it works

The VP systems all come standard with hoses, just connect and start transferring fluids.

Benefits

- Lightweight, portable systems
- Up to 20 Bar working pressure (VP-06 and VP-20)
- For use with many types of fluids, optional suction or pressure filter available
- · All VP- series come with hoses, just plug and play
- Checkvalve included in return hose to ensure one- way direction
- The perfect companion in your maintenance vehicle or workshop
- Available in 110V, 230V and 400V







TRIS VP SERIES OIL TRANSFER PUMPS

VP- series selection table			
MODEL	VP-05	VP-06	VP-20
I/O	3/8" x 3/8"	1/2" x 1/2"	1/2" x 1/2" (Quick couplings)
Weight	~ 9,2 KG	~ 16,5 KG	~ 19,0 KG
Size	~ 37 x 26 x 18cm	~ 60 x 26 x 46cm	~ 60 x 26 x 46cm
Bar	8 Bar max. working pressure	20 Bar max. working pressure	20 Bar max. working pressure
Temp.	Max. fluid temp: 80 °C	Max. fluid temp: 80 °C	Max. fluid temp: 80 °C
cSt.	10 - 460 cSt @ 40°C	10 - 460 cSt @ 40°C	10 - 460 cSt @ 40°C
Flow	5L./min	6L./min	20L./min
Hoses	2 x 3m includes checkvalve	2 x 3m includes checkvalve	2 x 3m includes checkvalve







